

H																																														
G																																														
F																																														
E																																														
D	<table><tr><td>SWITHC TESTED N. MWN3506</td><td>Not waterproof</td></tr><tr><td>VOLTAGE-DROP AFTER ASSEMBLY AT Pn AND Up<=30mV</td><td></td></tr><tr><td>NOMINAL VOLTAGE</td><td>12V DC</td></tr><tr><td>OPERATING VOLTAGE</td><td>9V - 14V</td></tr><tr><td>TESTING VOLTAGE</td><td>13V ±0,26V</td></tr><tr><td>TEMPERATURE RANGE</td><td>-30C° +80C° (bis +100C° max 1h) and 90% relative humidity</td></tr><tr><td>RATED LOAD</td><td>25W lamp load</td></tr><tr><td>MAX TESTING CURRENT</td><td>10A / 1 min</td></tr><tr><td>LIFE TEST 1</td><td>500.000 cycles at Pn and up(..)</td></tr><tr><td>LIFE TEST 2</td><td>100.000 cycles with 44W</td></tr><tr><td>OPERATIN FREQUENCY</td><td>6 cycles/min (2s on / 8s off)</td></tr></table>				SWITHC TESTED N. MWN3506	Not waterproof	VOLTAGE-DROP AFTER ASSEMBLY AT Pn AND Up<=30mV		NOMINAL VOLTAGE	12V DC	OPERATING VOLTAGE	9V - 14V	TESTING VOLTAGE	13V ±0,26V	TEMPERATURE RANGE	-30C° +80C° (bis +100C° max 1h) and 90% relative humidity	RATED LOAD	25W lamp load	MAX TESTING CURRENT	10A / 1 min	LIFE TEST 1	500.000 cycles at Pn and up(..)	LIFE TEST 2	100.000 cycles with 44W	OPERATIN FREQUENCY	6 cycles/min (2s on / 8s off)																				
SWITHC TESTED N. MWN3506	Not waterproof																																													
VOLTAGE-DROP AFTER ASSEMBLY AT Pn AND Up<=30mV																																														
NOMINAL VOLTAGE	12V DC																																													
OPERATING VOLTAGE	9V - 14V																																													
TESTING VOLTAGE	13V ±0,26V																																													
TEMPERATURE RANGE	-30C° +80C° (bis +100C° max 1h) and 90% relative humidity																																													
RATED LOAD	25W lamp load																																													
MAX TESTING CURRENT	10A / 1 min																																													
LIFE TEST 1	500.000 cycles at Pn and up(..)																																													
LIFE TEST 2	100.000 cycles with 44W																																													
OPERATIN FREQUENCY	6 cycles/min (2s on / 8s off)																																													
C																																														
B	<table><tr><td>REVISIONE / Revision</td><td colspan="3"></td><td></td><td></td></tr><tr><td>A</td><td colspan="3">Modificato codice, era 2000.02.3151</td><td>17/11/20</td><td>FNU LMP</td></tr><tr><td>RIF. REVISIONE / Revision ref.</td><td colspan="3">DESCRIZIONE REVISIONE DISEGNO / Design revision description</td><td>DATA / Date</td><td>DISEGNATO / Drawn by</td></tr></table>				REVISIONE / Revision						A	Modificato codice, era 2000.02.3151			17/11/20	FNU LMP	RIF. REVISIONE / Revision ref.	DESCRIZIONE REVISIONE DISEGNO / Design revision description			DATA / Date	DISEGNATO / Drawn by																								
REVISIONE / Revision																																														
A	Modificato codice, era 2000.02.3151			17/11/20	FNU LMP																																									
RIF. REVISIONE / Revision ref.	DESCRIZIONE REVISIONE DISEGNO / Design revision description			DATA / Date	DISEGNATO / Drawn by																																									
A	<table><tr><td colspan="2">MATERIALE: / Material:</td><td colspan="2">TRATTAMENTI TERMICI: / Heat treatments:</td></tr><tr><td colspan="2">STATO: / Condition:</td><td colspan="2">FINITURA: / Finishing:</td></tr><tr><td colspan="2">CARATTERISTICHE MECCANICHE: / Mechanical characteristics:</td><td colspan="2">MASSA (Kg) : / Weight (Kg) :</td></tr><tr><td colspan="2">Copyright © Domino S.r.l. - All rights reserved. Any reproduction, even partial and with any kind of instrument, is forbidden. No disclosure to third parties or to Domino competitors is allowed.</td><td colspan="2">TOLLERANZE GENERALI: / General tolerances: UNI EN-ISO 22768-mK</td></tr><tr><td colspan="2">DISEGNATO / Drawn by: NOME / Name: FNU DATA / Date: 17/11/2020</td><td colspan="2">RUGOSITA' Ra(µm): / Roughness Ra(µm): UNI EN-ISO 1302</td></tr><tr><td colspan="2">APPROVATO / Approved by: NOME / Name: LMP DATA / Date: 17/11/2020</td><td colspan="2">UNITA' DI MISURA (mm) / Unit of measure (mm)</td></tr><tr><td colspan="2">SCALA / Scale: 3:1</td><td colspan="2">DISEGNO PROVVISORIO N° / Draft N°: 1</td></tr><tr><td colspan="2">CLASSE FUNZIONALE / Functional cl.: 1</td><td colspan="2">DISEGNO CLIENTE: / Customer design:</td></tr><tr><td colspan="2">DISPOSITIVO - INTERR.STOP (N.C.)</td><td colspan="2">DISEGNO N° / Drawing code N°: 2000.20.3151</td></tr><tr><td colspan="2">domino S.r.l. Via delle Industrie, 16/18 SIRTORI - Fraz. Bevera 23896 (Lc) Italy</td><td colspan="2">MOD. / REV.: -01 A</td></tr></table>				MATERIALE: / Material:		TRATTAMENTI TERMICI: / Heat treatments:		STATO: / Condition:		FINITURA: / Finishing:		CARATTERISTICHE MECCANICHE: / Mechanical characteristics:		MASSA (Kg) : / Weight (Kg) :		Copyright © Domino S.r.l. - All rights reserved. Any reproduction, even partial and with any kind of instrument, is forbidden. No disclosure to third parties or to Domino competitors is allowed.		TOLLERANZE GENERALI: / General tolerances: UNI EN-ISO 22768-mK		DISEGNATO / Drawn by: NOME / Name: FNU DATA / Date: 17/11/2020		RUGOSITA' Ra(µm): / Roughness Ra(µm): UNI EN-ISO 1302		APPROVATO / Approved by: NOME / Name: LMP DATA / Date: 17/11/2020		UNITA' DI MISURA (mm) / Unit of measure (mm)		SCALA / Scale: 3:1		DISEGNO PROVVISORIO N° / Draft N°: 1		CLASSE FUNZIONALE / Functional cl.: 1		DISEGNO CLIENTE: / Customer design:		DISPOSITIVO - INTERR.STOP (N.C.)		DISEGNO N° / Drawing code N°: 2000.20.3151		domino S.r.l. Via delle Industrie, 16/18 SIRTORI - Fraz. Bevera 23896 (Lc) Italy		MOD. / REV.: -01 A			
MATERIALE: / Material:		TRATTAMENTI TERMICI: / Heat treatments:																																												
STATO: / Condition:		FINITURA: / Finishing:																																												
CARATTERISTICHE MECCANICHE: / Mechanical characteristics:		MASSA (Kg) : / Weight (Kg) :																																												
Copyright © Domino S.r.l. - All rights reserved. Any reproduction, even partial and with any kind of instrument, is forbidden. No disclosure to third parties or to Domino competitors is allowed.		TOLLERANZE GENERALI: / General tolerances: UNI EN-ISO 22768-mK																																												
DISEGNATO / Drawn by: NOME / Name: FNU DATA / Date: 17/11/2020		RUGOSITA' Ra(µm): / Roughness Ra(µm): UNI EN-ISO 1302																																												
APPROVATO / Approved by: NOME / Name: LMP DATA / Date: 17/11/2020		UNITA' DI MISURA (mm) / Unit of measure (mm)																																												
SCALA / Scale: 3:1		DISEGNO PROVVISORIO N° / Draft N°: 1																																												
CLASSE FUNZIONALE / Functional cl.: 1		DISEGNO CLIENTE: / Customer design:																																												
DISPOSITIVO - INTERR.STOP (N.C.)		DISEGNO N° / Drawing code N°: 2000.20.3151																																												
domino S.r.l. Via delle Industrie, 16/18 SIRTORI - Fraz. Bevera 23896 (Lc) Italy		MOD. / REV.: -01 A																																												